



# Core stacking tables **GEORG precisionstack 15-290**

---

transformer lines



mit uns **technisch überlegen**



## Your benefits

- > GEORG quality made in Germany
- > Sturdy construction and precision workmanship
- > Most precise and fast transformer core production
- > Reduced change-over and set-up times
- > Numerous different lamination positioning devices (e.g. stacking pins, corner stops, side stops, ...), individually selected and designed as per customer's requirements
- > Well thought-out adjustment and auxiliary facilities
- > Optionally available Press and Strapping Units (for **GEORG precisionstack 40 and larger**)
- > Superb support by GEORG



## Main technical data

Size index	15	25	30	40	70	110	200	290
Capacity	15 tons	25 tons	30 tons	40 tons	70 tons	110 tons	200 tons	290 tons
Number of legs	3	3	3	3	3	5	5	5
Strip width	60 mm to 600 mm	60 mm to 640 mm	80 mm to 700 mm	80 mm to 840 mm	100 mm to 1,000 mm	300 mm to 1,000 mm	300 mm to 1,500 mm	510 mm to 1,800 mm
Leg to leg (center)	550 mm to 1,200 mm	550 mm to 1,380 mm	600 mm to 1,400 mm	650 mm to 1,800 mm	650 mm to 2,100 mm	1,000 mm to 2,300 mm	1,000 mm to 3,000 mm	1,500 mm to 4,000 mm
Leg length (center)	1,100 mm to 2,250 mm	1,150 mm to 2,400 mm	1,200 mm to 2,800 mm	1,400 mm to 3,500 mm	1,500 mm to 4,000 mm	1,800 mm to 4,000 mm	1,800 mm to 3,500 mm	2,500 mm to 4,400 mm
Yoke length (center)	1,100 mm to 2,400 mm	1,100 mm to 2,760 mm	1,200 mm to 2,800 mm	1,300 mm to 3,600 mm	1,300 mm to 4,200 mm	2,000 mm to 7,500 mm	2,000 mm to 9,600 mm	3,000 mm to 12,000 mm
Max. stacking height	600 mm	640 mm	640 mm	1,000 mm	1,000 mm	1,000 mm	1,500 mm	1,800 mm
Upending	hydraulic			Crane+skid or hydraulic				

Core stacking tables  
**GEORG precisionstack 15-290**

Heinrich Georg GmbH  
 Maschinenfabrik  
 Langenauer Straße 12  
 57223 Kreuztal, Germany

Phone +49 2732 779-180  
 Fax +49 2732 779-294  
 Email [trafo@georg.com](mailto:trafo@georg.com)  
 Web [georg.com](http://georg.com)



mit uns technisch überlegen